

SQ50B1

Capacity

- Pipe: ½"-2"(12mm-50mm)

Technical Specifications

- Motor: 750W induction, 50/60Hz
- Switch: ON/OFF heavy duty switch, foot switch and FOR/OFF/REV switch is optional
- Spindle Speed: 24 RPM
- Front Chuck: Hammer type with replaceable rocker action jaw inserts.
- Rear Centering Device: Cam action.
- Oiling System: Through die head, with integral oil reservoir.
- Pump: Self-priming constant flow.

Ordering Information

Catalog No.	Model No.	Description	Spindle Speed RPM	Pipe Threading Capacity		N.W (kg)
				in.	mm.	
35012	SQ50B1	110V, 60Hz	24	½-2	12-50	
35011	SQ50B1	220V, 50Hz	24	½-2	12-50	



SQ50C1

Capacity

- Pipe: ½"-2"(12mm-50mm)

Technical Specifications

- Motor: 900W induction, 50/60Hz
- Switch: ON/OFF heavy duty switch, foot switch and FOR/OFF/REV switch is optional
- Spindle Speed: 25 RPM
- Front Chuck: Hammer type with replaceable rocker action jaw inserts.
- Rear Centering Device: Cam action.
- Oiling System: Through die head, with integral oil reservoir.
- Pump: Self-priming constant flow.

Ordering Information

Catalog No.	Model No.	Description	Spindle Speed RPM	Pipe Threading Capacity		N.W (kg)
				in.	mm.	
36012	SQ50C1	110V, 60Hz	25	½-2	12-50	
36011	SQ50C1	220V, 50Hz	25	½-2	12-50	

